

Link to the product: <https://www.skyrc.eu/skyrc-b6ac-v2-genuine-charger-acdc-dual-power-p-190.html>

SkyRC B6AC V2 Genuine charger AC/DC Dual Power



| | |
|---------------|----------------------|
| Price | 54.52 Euro |
| Availability | Not available |
| Shipping time | 24 hours |
| Number | 188 |
| Producer code | SK-100008 |
| Manufacturer | SkyRC |

Product description

SkyRC B6AC V2 Genuine charger AC/DC Dual Power

SKYRC B6AC V2 is the upgraded version for well-known iMAX B6AC. Compared with iMAX B6AC, it is more accurate and stable and also has some new features and functions. Users could set the terminal voltage by themselves and connect it to PC for PC control and firmware upgrade. What's more, users could also use it as Lithium Battery Meter and Battery Internal Resistance Meter. There are Automatic Charging Current Limit, Capacity Limit, Temperature Threshold and Processing Time Limit which makes the charger safer than V1. SKYRC B6AC V2 is a high-performance, micro processor control charge/discharge station with battery management suitable for use with all current battery types, with integral equalizer for six-cell Lithium- Polymer (LiPo), Lithium High Voltage, Lithium iron phosphate (LiFe) and Lithium-Ion (Lilon) batteries; maximum 6A charge current and maximum 50W charge power.

Specifications:

Specifications

| | |
|-------------------------|-------------------|
| AC Input Voltage | 100-240V |
| DC Input Voltage | DC11-18V |
| Circuit Power | Max Charge: 50W |
| | Max Discharge: 5W |
| Charge Current Range | 0.1-6.0A |
| Discharge Current Range | 0.1-2.0A |
| LiPo/LiFe/LiIon Cells | 1-6S |
| NiMH/NiCd Cells | 1-15S |
| Pb battery Voltage | 2-20V |
| Net Weight | 632g |

Size

Length : 144mm
Width : 135mm
Height : 36mm

