



## SkyRC e455 Multi Chemistry Charger Completely upgraded, re-engineered 2-4S 50W / 4A LiPo LiFe LiHv

Price	<b>28.33 Euro</b>
Availability	<b>Available in stock</b>
Shipping time	<b>24 hours</b>
Producer code	<b>SK-100170</b>
Manufacturer	<b>SkyRC</b>

### Product description

## SkyRC e455 Multi Chemistry Charger Completely upgraded, re-engineered 2-4S 50W / 4A LiPo LiFe LiHv

### Light touch button: multiple-state adjusting made easy

We put the brains of the classic E450 and reengineer body of with multiple-state button replacing the slide switch for better control experience. e455 allows choosing battery type & charge current. by pushing buttons. Even if it is your first programmable charger, you'll find using is a breeze: you should connect balance ports before charging LiPo/LiHV/LiHV battery.

### 50 W 4A

Multi Chemistry Charger SkyRC e455 Charger is an economical, high-quality, universal 100-240V AC balance charger designed for charging LiPo, LiFe, and LiHV batteries from 2-4 cells in balance mode. It also can charge 6-8S NiMH batteries. The circuit power is 50W, and the max charge current can reach 4A. Four kinds of charge current 1A/2A/3A/4A can be selected. You could choose the proper charge current according to the battery capacity.

### Embedded XT60 Battery Connector

By embedding the XT60 battery connector, it gets more convenient & safe for charging the most popular battery with XT60 connectors and avoids any possibilities of reverse polarity.

### Package:

### Specyfications:

AC Input: 100-240V

Battery Type: LiPo/LiFe/LiHV/NiMH

---

Cell Count:  
LiPo/LiFe/LiHV: 2-4S  
NiMH: 6-8S  
Charge Current: 1A/2A/3A/4A  $\pm$  10%  
Cell Terminate Voltage:  
LiPo 4.2V $\pm$ 0.02V  
LiHV: 4.35V $\pm$ 0.02V LiFe: 3.6V $\pm$ 0.02V  
NiMH: -  $\Delta$ V  
Circuit Power: 50W  
Current Drain for Balancing: 300mA  
Case Material: Plastic  
Case Size: 110x70x40mm  
Weight: 191g

Specyfifications:

## Specyfifications:

AC Input: 100-240V  
Battery Type: LiPo/LiFe/LiHV/NiMH  
Cell Count:  
LiPo/LiFe/LiHV: 2-4S  
NiMH: 6-8S  
Charge Current: 1A/2A/3A/4A  $\pm$  10%  
Cell Terminate Voltage:  
LiPo 4.2V $\pm$ 0.02V  
LiHV: 4.35V $\pm$ 0.02V LiFe: 3.6V $\pm$ 0.02V  
NiMH: -  $\Delta$ V  
Circuit Power: 50W  
Current Drain for Balancing: 300mA  
Case Material: Plastic  
Case Size: 110x70x40mm  
Weight: 191g