Data current as of: 13-11-2026 01:16

Link to the product: https://www.skyrc.eu/skyrc-nc3000-octa-charger-48w3a-aaaaa-nimhnicd-p-775.html



SkyRC NC3000 Octa Charger 48W/3A AA/AAA NiMH/NiCD

Price	**102.38 Euro**
Availability	**Available in stock**
Shipping time	**24 hours**
Producer code	**SK-100228**
Manufacturer	**SkyRC**

Product description

SkyRC NC3000 Octa Charger 48W/3A AA/AAA NiMH/NiCD

Eight Slots. Energy Multiplied!!

Featuring eight independent AA/AAA slots, each with its own charging mode, NC3000 Octa gives you complete control—from fast power to precise battery management. With an adjustable current from 0.20A to 3.0A, you can set the ideal speed for every battery.

Omni 7 Modes. Truly Versatile.

This charger supports 7 working modes:: Charge, Discharge, Activate, Cycle, MaxBoost, Turbo oraz Three-stage Charge

PD Input. Punch Amplified.

When paired with the mainstream PD (Power Delivery) input, NC3000 Octa delivers fast and efficient charging. With sufficient power input, this desktop powerhouse can charge each cell at up to 3000 mA, or discharge eight batteries simultaneously at 2500 mA per cell.

Intuitive LED indicators Status. At a Glance.

This Pro NiMH & NiCD Charger features intuitive LED lights that let you see your battery status at a glance. Here’s what each light means:

Warm Up. Perform Up.

With MaxBoost, fully charge the battery, discharge it to your target level, and top it off before racing. Or use 3-Stage Charging, starting with a low current and finishing with a higher one to raise temperature and reduce internal resistance. Both modes are designed for racing, helping your battery reach optimal temperature, lower IR, and maximum punch before the start.

Match Well. Maximize Power.

Through its discharge test mode, the charger can generate and display real-time discharge curves, helping you visually identify and match cells with consistent performance, maximizing the output and efficiency of your devices.

Charge. Stay Cool.

The intelligent triple-fan system adjusts speed on demand, striking the perfect balance between high airflow and low noise. Each slot features its own ventilation channel, delivering even and effective cooling to reduce heat-related performance loss and keep your batteries more stable and longer lasting.

Go Appy. Go Smart.

With built-in Bluetooth, NC3000 Octa connects directly to your smartphone. The free SkyCharger app offers a more intuitive experience with a graphic interface displaying all data and a charging graph. With recorded data on the app, you can easily analyze your battery's performance! *Scan the QR code below to download the SkyCharger app.

Package:

1. SkyRC NC3000 octa
2. Manual

Specification:

Size and Weight
Case Size: 112 x 149 x 44 mm
Weight: Approx. 330g
Display
Display Type: TN
Size: 1.77 inch
Panel Active Area: 43.20*57.60mm
Resolution: 160x128 Pixel
Number of Colors: 262K
Charge and Discharge
Input Power: PD 65W
Quick Charge Protocol: PD3.0
Battery Type: NiMH/NiCD
Battery Size: AA/AAA
Charge Power: Max. 48W
Discharge Power: Max. 30W
Charge Rate: 0.20-3.00A w/ increments of 0.10A
Discharge Rate: 0.20-2.50A w/ increments of 0.10A
Trickle Charge Rate: 10-300mA & OFF
Target Volt.: 1.25-1.80V
Discharge Cut-Off Volt.: 0.50-1.40V
Supported Capacity: 100-5000mAh
-△V: 1-20mV
Working and Storage
Operating temperature: 0℃-40℃
Working humidity: 5%-75%
Storage temperature: -10℃-70℃
Storage humidity: 5%-75%