Data current as of: 14-11-2026 01:25

Link to the product:
https://www.skyrc.eu/skyrc-t100-dual-balance-charger-discharger-for-lipoliionlifelihv-battery-2-4s-2x50w-5a-p-734.html



# SKYRC T100 DUAL Balance Charger Discharger for LiPo/LiIon/LiFe/LiHV Battery 2-4S 2x50W 5A

| | |
|---|---|
| Price | **45.00 Euro** |
| Availability | **Available in stock** |
| Shipping time | **24 hours** |
| Producer code | **SK-100162** |
| EAN | **6930460006011** |
| Manufacturer | **SkyRC** |

Product description

# SKYRC T100 DUAL Balance Charger Discharger for LiPo/LiIon/LiFe/LiHV Battery 2-4S 2x50W 5A

## Multi-purpose for Most Chemistries With Compact Size

SkyRC T100 is a twin-channel charger with two independent circuits which can charge batteries of varying chemistries (LiPo / LiFe / LiIon / LiHV / NiMH / NiCd / Pb) simultaneously. Its sleek design allows easy front-loading plug-in convenience of balancing and XT60 ports. It is not only compact in size but also powerful in output with maximum 100W charging power and 5A charging current which makes charging more sufficient. With the new AGM and cold charge modes, the user is free to charge their PB and AGM batteries in cold days.

## Twin-channel Charger

SkyRC T100 allows you to plug 2 batteries into one charger simultaneously, and it will intelligently and automatically initiate the charging of 2 batteries at once to their maximum capacity. To top it all, the batteries being charged do not even need to have the same configuration. You can connect different chemistry(NiMH / NiCd / LiPo / LiFe / LiIon / LiHV / Pb)batteries into any of the charging ports.

## Higher accuracy with three decimal places for battery voltage

The charger firmware is highly optimized, it displays battery voltages with three decimal places during the charging process.

## AGM & Cold Charge Modes for PB Battery

SkyRC T100 can charge AGM(Absorbent Glass Mat) )battery and also can be used for charging PB battery at very low temperatures.

# Embedded XT60 Battery Connector

By embedding the XT60 battery connector in the charger, it gets more convenient & safe for charging the most popular battery with XT60 connector and avoid the possibilities of reverse polarity for it.

# Package

1. Charger SkyRC T100
2. Power cord

# Specyfications:

Case Material: Plastic
Case Size: 90x100x127mm
Weight: 500g
Display Type: 2x16LCD
Display Backlight: Blue
Input Voltage: AC 100-240V
Charge Wattage: 50Wx2
Battery Types/Cells: LiPo/LiFe/LiIon/LiHV: 2-4 cells
NiMH/NiCd: 6-8 cells
Pb:6/12V
Battery Capacity Range: LiPo/LiIon/LiFe/LiHV:100-50000mAh
NiMH/NiCd:100-50000mAh
Pb: 100-50000mAh
Charge Voltage:
LiPo: 4.18-4.25V/cell
LiFe: 3.58-3.7V/cell
LiIon: 4.08-4.2V/cell
LiHV: 4.25-4.35V/cellNiMH/NiCd: detection: 3-15mV/cell ; Default: 4mV/cell
Discharge Cut-off Voltage:
LiPo:3.0-3.3V/cell
LiFe:2.6-2.9V/cellLiIon: 2.9-3.2V/cell
LiHV: 3.1-3.4V/cellNiMH/NiCd:0.1-1.1V/cell
Charge Current: 0.1A-5.0A
Balance Cells: 2-4 cells
Balance Current: 300mA/cell
Safety Timer: 1-720minutes & OFF
Charge Method:CC/CV for Lithium batteries.
CC/CV and float charge for PB batteries.

Specyfications:

# Specyfications:




Case Material: Plastic
Case Size: 90x100x127mm
Weight: 500g
Display Type: 2x16LCD
Display Backlight: Blue
Input Voltage: AC 100-240V
Charge Wattage: 50Wx2
Battery Types/Cells: LiPo/LiFe/LiIon/LiHV: 2-4 cells
NiMH/NiCd: 6-8 cells
Pb:6/12V
Battery Capacity Range: LiPo/LiIon/LiFe/LiHV:100-50000mAh
NiMH/NiCd:100-50000mAh
Pb: 100-50000mAh
Charge Voltage:
LiPo: 4.18-4.25V/cell
LiFe: 3.58-3.7V/cell
LiIon: 4.08-4.2V/cell
LiHV: 4.25-4.35V/cellNiMH/NiCd: detection: 3-15mV/cell ; Default: 4mV/cell
Discharge Cut-off Voltage:
LiPo:3.0-3.3V/cell
LiFe:2.6-2.9V/cellLiIon: 2.9-3.2V/cell
LiHV: 3.1-3.4V/cellNiMH/NiCd:0.1-1.1V/cell
Charge Current: 0.1A-5.0A
Balance Cells: 2-4 cells
Balance Current: 300mA/cell
Safety Timer: 1-720minutes & OFF
Charge Method:CC/CV for Lithium batteries.
CC/CV and float charge for PB batteries.