



SKYRC T100 DUAL Balance Charger Discharger for LiPo/Lilon/LiFe/LiHV Battery 2-4S 2x50W 5A

Price	45.00 Euro
Availability	Available in stock
Shipping time	24 hours
Producer code	SK-100162
EAN	6930460006011
Manufacturer	SkyRC

Product description

SKYRC T100 DUAL Balance Charger Discharger for LiPo/Lilon/LiFe/LiHV Battery 2-4S 2x50W 5A

Multi-purpose for Most Chemistries With Compact Size

SkyRC T100 is a twin-channel charger with two independent circuits which can charge batteries of varying chemistries (LiPo / LiFe / Lilon / LiHV / NiMH / NiCd / Pb) simultaneously. Its sleek design allows easy front-loading plug-in convenience of balancing and XT60 ports. It is not only compact in size but also powerful in output with maximum 100W charging power and 5A charging current which makes charging more sufficient. With the new AGM and cold charge modes, the user is free to charge their PB and AGM batteries in cold days.

Twin-channel Charger

SkyRC T100 allows you to plug 2 batteries into one charger simultaneously, and it will intelligently and automatically initiate the charging of 2 batteries at once to their maximum capacity. To top it all, the batteries being charged do not even need to have the same configuration. You can connect different chemistry(NiMH / NiCd / LiPo / LiFe / Lilon / LiHV / Pb)batteries into any of the charging ports.

Higher accuracy with three decimal places for battery voltage

The charger firmware is highly optimized, it displays battery voltages with three decimal places during the charging process.

AGM & Cold Charge Modes for PB Battery

SkyRC T100 can charge AGM(Absorbent Glass Mat))battery and also can be used for charging PB battery at very low temperatures.

Embedded XT60 Battery Connector

By embedding the XT60 battery connector in the charger, it gets more convenient & safe for charging the most popular battery with XT60 connector and avoid the possibilities of reverse polarity for it.

Package

1. Charger SkyRC T100
2. Power cord

Specyfifications:

Case Material: Plastic
Case Size: 90x100x127mm
Weight: 500g
Display Type: 2x16LCD
Display Backlight: Blue
Input Voltage: AC 100-240V
Charge Wattage: 50Wx2
Battery Types/Cells: LiPo/LiFe/Lilon/LiHV: 2-4 cells
NiMH/NiCd: 6-8 cells
Pb: 6/12V
Battery Capacity Range: LiPo/Lilon/LiFe/LiHV: 100-50000mAh
NiMH/NiCd: 100-50000mAh
Pb: 100-50000mAh
Charge Voltage:
LiPo: 4.18-4.25V/cell
LiFe: 3.58-3.7V/cell
Lilon: 4.08-4.2V/cell
LiHV: 4.25-4.35V/cell NiMH/NiCd: detection: 3-15mV/cell ; Default: 4mV/cell
Discharge Cut-off Voltage:
LiPo: 3.0-3.3V/cell
LiFe: 2.6-2.9V/cell Lilon: 2.9-3.2V/cell
LiHV: 3.1-3.4V/cell NiMH/NiCd: 0.1-1.1V/cell
Charge Current: 0.1A-5.0A
Balance Cells: 2-4 cells
Balance Current: 300mA/cell
Safety Timer: 1-720minutes & OFF
Charge Method: CC/CV for Lithium batteries.
CC/CV and float charge for PB batteries.

Specyfifications:

Specyfifications:



Case Material: Plastic
 Case Size: 90x100x127mm
 Weight: 500g
 Display Type: 2x16LCD
 Display Backlight: Blue
 Input Voltage: AC 100-240V
 Charge Wattage: 50Wx2
 Battery Types/Cells: LiPo/LiFe/Lilon/LiHV: 2-4 cells
 NiMH/NiCd: 6-8 cells
 Pb: 6/12V
 Battery Capacity Range: LiPo/Lilon/LiFe/LiHV: 100-50000mAh
 NiMH/NiCd: 100-50000mAh
 Pb: 100-50000mAh
 Charge Voltage:
 LiPo: 4.18-4.25V/cell
 LiFe: 3.58-3.7V/cell
 Lilon: 4.08-4.2V/cell
 LiHV: 4.25-4.35V/cell NiMH/NiCd: detection: 3-15mV/cell ; Default: 4mV/cell
 Discharge Cut-off Voltage:
 LiPo: 3.0-3.3V/cell
 LiFe: 2.6-2.9V/cell Lilon: 2.9-3.2V/cell
 LiHV: 3.1-3.4V/cell NiMH/NiCd: 0.1-1.1V/cell
 Charge Current: 0.1A-5.0A
 Balance Cells: 2-4 cells
 Balance Current: 300mA/cell
 Safety Timer: 1-720minutes & OFF
 Charge Method: CC/CV for Lithium batteries.
 CC/CV and float charge for PB batteries.