Link to the product: https://www.skyrc.eu/skyrc-infrared-termometer-p-272.html

SkyRC Infrared termometer

Price	41.62 Euro
Availability	Not available
Shipping time	24 hours
Number	270
Producer code	SK-500016
Manufacturer	SkyRC

Product description

This is a non-contact infrared thermometer specifically designed for use with R/C engines, electronic speed controllers and etc.

Simply aim the infrared thermometer at the target and press the measurement button to quickly and easily displayed

- High accuracy and high speed infrared sensor
- Four modes for temperature records: Quick Mode / Scan Mode / Max. Value / Min. Value

 The infrared emissivity coe A large LCD can display ter read 	mperature from -40°C(-40°F) to 380°C(716°F) efficient can be adjusted mperature, emissivity coefficient and battery's capacity, etc., and applied with back and powered by 2 x AAA batteries (Battery Excluded)
	neasure temperatures. Point the sensor located on the top end of the gauge neasured, and do one of the following:
1. Quick Mode:	
	Press the "MEASURE" button once for an instantaneous temperature reading to be shown on-screen.
2. Scan Mode:	
	Moving the aluminum cup as close as possible to the target.Press and hold the "MEASURE" button to read temperatures continually. The temperature onscreen will be updated continually. Release "MEASURE" button will cause the last reading to remain locked onscreen.

generated by the shopGold

3.Maximum Temperature Mode:

while the button is being held.

4.Minimum Temperature ModePoint the aluminum cup to the

object being measured, and press

Point the aluminum cup to the **abjectobeithe 性性自然使用的** and hold the "MEASURE" button and the thermometer will display and looked the the point the display and looked the hottest or MAX

temperature that is observed

This thermometer can temporarily store minimum or maximum temperatures. Turn the unit on by pressing the M button once for the maximum function or twice for minimum. The appropriate MAX or MIN icon will display in the

Specifications:

Dimension	121x40x39.6mn
Weight	75g
Operation Voltage	AAA battery X 2
Operation Current	≤40ma@2.0V
Operation Temperature	0-40°C
Current Drain	≤25ua@3V

Precision	-40°C-0°C +/-1°C
	60°C-120°C +/-1°C
	180°C-240°C +/-3°C
Adjustable Range for Infrared	0.01-1
Emission Frequency	