

Link to the product: <https://www.skyrc.eu/skyrc-toro-x8-1750kv-9t-for-18-buggy-sensorless-p-283.html>

SkyRC TORO X8 1750KV 9T FOR 1/8 BUGGY sensorless



Price	64.05 Euro
Availability	Not available
Shipping time	24 hours
Number	281
Producer code	SK-400001-11
Manufacturer	SkyRC

Product description

TORO X8
BUGGY



- CNC Machined T6 Billet Aluminum Heatsink Can
- 18 Slots Stator Hi-torque Motor Design
- Rotor-6 Pole Neodymium Sintered Magnets
- High RPM & Supersized Bearings
- High Purity Copper Windings for Maximizes Efficiency
- Precision Engineered for Maximum Energy Conversion
- Stator-Super Thin (0.2mm) Laminations
- Super High Current Silicon Wires
- Super Strength 5mm Shaft
- Removable /Replaceable Rotor

Item	KV (RPM/VOLT)	Watts	Max Voltage	Max Current	Internal Resistance (ohm)	Max RPM	Length	Outer Diameter /W/Fins	Net Weight	Shaft Diameter	Shaft Length	Turns	Rotor (Pole)	Stator Length	Lead Wire Size	Max Efficiency (%)
SK-400001-03	2650	2200	18V	125A	0.0062	50000	68mm	42.8mm	375g	Φ5mm	15mm	6T	6Poles	40mm	12#	86%-90%
SK-400001-10	2250	2200	22V	100A	0.0075	50000	68mm	42.8mm	375g	Φ5mm	15mm	7T	6Poles	40mm	12#	86%-90%
SK-400001-04	1900	2200	26V	85A	0.0083	50000	68mm	42.8mm	375g	Φ5mm	15mm	8T	6Poles	40mm	12#	86%-90%
SK-400001-11	1750	2200	28V	78A	0.0103	50000	68mm	42.8mm	375g	Φ5mm	15mm	9T	6Poles	40mm	12#	86%-90%

Specifications:

Item	KV (RPM/VOLT)	Watts	Max Voltage	Max Current	Internal Resistance (ohm)	Max RPM	Length	Outer Diameter /W/Fins	Net Weight	Shaft Diameter	Shaft Length	Turns	Rotor (Pole)	Stator Length	Lead Wire Size	Max Efficiency (%)
SK-400001-03	2650	2200	18V	125A	0.0062	50000	68mm	42.8mm	375g	Φ5mm	15mm	6T	6Poles	40mm	12#	86%-90%
SK-400001-10	2250	2200	22V	100A	0.0075	50000	68mm	42.8mm	375g	Φ5mm	15mm	7T	6Poles	40mm	12#	86%-90%
SK-400001-04	1900	2200	26V	85A	0.0083	50000	68mm	42.8mm	375g	Φ5mm	15mm	8T	6Poles	40mm	12#	86%-90%
SK-400001-11	1750	2200	28V	78A	0.0103	50000	68mm	42.8mm	375g	Φ5mm	15mm	9T	6Poles	40mm	12#	86%-90%