

Link to the product: <https://www.skyrc.eu/skyrc-toro-x8p-1850kv-8t-for-18-buggy-sensorless-p-284.html>

SkyRC TORO X8P 1850KV 8T FOR 1/8 BUGGY sensorless



Price	67.14 Euro
Availability	Not available
Shipping time	24 hours
Number	282
Producer code	SK-400001-13
Manufacturer	SkyRC

Product description

TORO X8T
TRUGGY



1/8 Scale
BRUSHLESS MOTOR

- CNC Machined T6 Billet Aluminum Heatsink Can
- 18 Slots Stator Hi-torque Motor Design
- Rotor-6 Pole Neodymium Sintered Magnets
- High RPM & Supersized Bearings
- High Purity Copper Windings for Maximizes Efficiency
- Precision Engineered for Maximum Energy Conversion
- Stator-Super Thin (0.2mm) Laminations
- Super High Current Silicon Wires
- Super Strength 5mm Shaft
- Removable /Replaceable Rotor

Item	KV (RPM/ VOLT)	Watts	Max Voltage	Max Current	Internal Resistance (ohm)	Max RPM	Length	Outer Diameter /W/Fins	Net Weight	Shaft Diameter	Shaft Length	Turns	Rotor (Pole) Length	Stator Length	Lead Wire Size	Max Efficiency (%)
SK-400001-05	2250	2500	22V	113A	0.0073	50000	74mm	42.8mm	435g	Φ5mm	15mm	6T	6Poles	46mm	12#	86%-90%
SK-400001-12	1900	2500	26V	96A	0.0095	50000	74mm	42.8mm	435g	Φ5mm	15mm	7T	6Poles	46mm	12#	86%-90%
SK-400001-13	1650	2500	30V	83A	0.0135	50000	74mm	42.8mm	435g	Φ5mm	15mm	8T	6Poles	46mm	12#	86%-90%
SK-400001-14	1500	2500	33V	75A	0.0186	50000	74mm	42.8mm	435g	Φ5mm	15mm	9T	6Poles	46mm	12#	86%-90%

Specifications:

Item	KV (RPM/ VOLT)	Watts	Max Voltage	Max Current	Internal Resistance (ohm)	Max RPM	Length	Outer Diameter /W/Fins	Net Weight	Shaft Diameter	Shaft Length	Turns	Rotor (Pole) Length	Stator Length	Lead Wire Size	Max Efficiency (%)
SK-400001-05	2250	2500	22V	113A	0.0073	50000	74mm	42.8mm	435g	Φ5mm	15mm	6T	6Poles	46mm	12#	86%-90%
SK-400001-12	1900	2500	26V	96A	0.0095	50000	74mm	42.8mm	435g	Φ5mm	15mm	7T	6Poles	46mm	12#	86%-90%
SK-400001-13	1650	2500	30V	83A	0.0135	50000	74mm	42.8mm	435g	Φ5mm	15mm	8T	6Poles	46mm	12#	86%-90%
SK-400001-14	1500	2500	33V	75A	0.0186	50000	74mm	42.8mm	435g	Φ5mm	15mm	9T	6Poles	46mm	12#	86%-90%